

Walk-Behind Power Trowels



The world's best-selling power trowels

Construction Starts Here

www.multiquip.com



Walk-Behind Power Trowels

Multiquip's Whiteman-Series Power Trowels continue to be the number one choice of the concrete industry. With over 60 years of manufacturing experience, no other power trowel can match our quality, reliability or performance.

A complete range of trowels is available with operating widths ranging from 24" to 48" and rotor speeds up to 180-RPM.

Each trowel is tested as it comes off the assembly line to ensure every machine meets our quality standards.

C-Series 24" Width

Compact design makes it ideal for finishing around plumbing pipes and edges. Features a 4.0-HP Honda engine, manual clutch and folding QuickPitch handle.



M-Series 30" Width

Versatile trowel provides good coverage and is compact enough to fit through most doorways.



J-Series 36" Width

Our most popular mid-size trowel. Generous coverage and performance are trademarks of this proven performer.



E-Series 36" Width

Reduced rotor speeds provide smooth application of epoxy coatings. Lightweight aluminum guard ring and spider assembly reduce operating weight for optimum performance.



HP-Series 36" and 46" Widths

Extra horsepower for the toughest applications. The HPL-Series provides the extra torque needed for pan floating applications. The HPH-Series features high rotor speeds necessary for burnishing slabs.



HD-Series 48" Width

Features our heavy-duty gearbox and spider assembly along with high-horsepower Honda engines. The 13-HP model features a CVT clutch that spins the rotor to a top speed of 180-RPM.



Setting the standard for more than 60 years

Trowel Handles

Every handle is designed with both ergonomics and performance in mind.

Features include greater leverage and height adjustments for improved comfort and reduced operator fatigue. Our new motorcycle-style throttle design makes increasing or decreasing operating speed as easy as a twist of the wrist.



Standard Handle

A favorite of contractors who prefer to have infinite blade pitch control. The large star wheel makes it easy to increase or decrease blade pitch to the desired angle.



Quick-Pitch™ Handle

A patented design enables the operator to react quickly to changing concrete conditions. Blade pitch is raised or lowered in 1/8" increments by squeezing the latching lever.



Maximize your trowel performance with genuine Whiteman blades!

A full selection of blades is available including QuickChange and heavy-duty Enduro models.

B-Series

46" Width - The Classic.

High horsepower engines and nearly 4-ft. of rotor coverage have made this trowel the favorite of concrete contractors for generations.

High-capacity gearbox

Safety shut-off switch

Ergonomic throttle control

Height adjustment for handlebar

Optional Quick-Pitch™ blade adjustment

Heavy-duty centrifugal clutch (manual clutch optional)

Removable weights

Long-lasting spider assembly

Stabilizer ring



Walk-Behind Power Trowel Specifications

| SERIES | MODEL | BLADES | RING DIAMETER IN | RING DIAMETER CM | ENGINE | HP | ROTOR RPM | OPER. WT. LBS | OPER. WT. KG | SHIP WT. LBS | SHIP WT. KG |
|------------|---------------|--------|------------------|------------------|------------------------------|------|-----------|---------------|--------------|--------------|-------------|
| C-SERIES | CA-4-4-H | 4 | 24 | 61 | Honda | 4.0 | 70-130 | 125.0 | 57.0 | 145.0 | 66.0 |
| M-SERIES | M-4-5BS | 4 | 30 | 76 | Briggs & Stratton | 5.0 | 60-100 | 136.0 | 62.0 | 176.0 | 80.0 |
| | M-4-6R | 4 | 30 | 76 | Robin | 6.0 | 60-100 | 141.0 | 64.0 | 181.0 | 82.0 |
| | M-4-6RM | 4 | 30 | 76 | Robin, manual clutch | 6.0 | 60-120 | 141.0 | 64.0 | 181.0 | 82.0 |
| | M-4-5H | 4 | 30 | 76 | Honda | 5.5 | 60-100 | 143.0 | 65.0 | 183.0 | 83.0 |
| | M-4-5HM | 4 | 30 | 76 | Honda, manual clutch | 5.5 | 60-125 | 143.0 | 65.0 | 183.0 | 83.0 |
| J-SERIES | JA-4-5BS | 4 | 36 | 90 | Briggs & Stratton | 5.0 | 60-100 | 143.0 | 65.0 | 183.0 | 83.0 |
| | JA-4-6R | 4 | 36 | 90 | Robin | 6.0 | 60-100 | 148.0 | 67.0 | 188.0 | 85.0 |
| | JA-4-6RM | 4 | 36 | 90 | Robin, manual clutch | 6.0 | 60-120 | 148.0 | 67.0 | 188.0 | 85.0 |
| | JA-4-5H | 4 | 36 | 90 | Honda | 5.5 | 60-100 | 150.0 | 68.0 | 190.0 | 86.0 |
| | JA-4-5HM | 4 | 36 | 90 | Honda, manual clutch | 5.5 | 60-125 | 150.0 | 68.0 | 190.0 | 86.0 |
| | J-4-2E | 4 | 36 | 90 | 115/230V 60 Hz 1Ø Elect. | 2.0 | 93.0 | 146.0 | 66.0 | 186.0 | 84.0 |
| | J-4-2E-50 | 4 | 36 | 90 | 220V 50 Hz 1Ø Elect. | 2.0 | 77.0 | 146.0 | 66.0 | 186.0 | 84.0 |
| B-SERIES | BA-4-8BS | 4 | 46 | 117 | Briggs & Stratton | 8.0 | 60-125 | 228.0 | 103.0 | 278.0 | 126.0 |
| | BA-4-8R | 4 | 46 | 117 | Robin | 9.0 | 60-125 | 237.0 | 107.0 | 287.0 | 130.0 |
| | BA-4-8RM | 4 | 46 | 117 | Robin, manual clutch | 9.0 | 60-145 | 237.0 | 107.0 | 287.0 | 130.0 |
| | BA-4-8H | 4 | 46 | 117 | Honda | 8.0 | 60-125 | 242.0 | 110.0 | 292.0 | 132.0 |
| | BA-4-8HM | 4 | 46 | 117 | Honda, manual clutch | 8.0 | 60-145 | 242.0 | 110.0 | 292.0 | 132.0 |
| | B-4-2E | 4 | 46 | 117 | 115/230V 60 Hz 1Ø Elect. | 2.0 | 108.0 | 179.0 | 81.0 | 229.0 | 104.0 |
| E-SERIES | E-4-1E-50 | 4 | 36 | 90 | 220V 50 Hz 1Ø Electric | 1.0 | 46.0 | 112.0 | 51.0 | 152.0 | 69.0 |
| | E-4-1EV | 4 | 36 | 90 | 115V 60 Hz 1Ø Electric | 1.0 | 55.0 | 112.0 | 51.0 | 152.0 | 69.0 |
| | E-4-5H | 4 | 36 | 90 | Honda | 5.5 | 30-55 | 127.0 | 58.0 | 167.0 | 76.0 |
| HPL-SERIES | HPLA-36-4-8R | 4 | 36 | 90 | Robin | 8.0 | 75-118 | 166.0 | 75.0 | 206.0 | 93.0 |
| | HPLA-36-4-8H | 4 | 36 | 90 | Honda | 8.0 | 55-118 | 171.0 | 77.0 | 211.0 | 96.0 |
| | HPLA-46-4-11H | 4 | 46 | 117 | Honda | 11.0 | 50-108 | 245.0 | 111.0 | 310.0 | 141.0 |
| HPH-SERIES | HPHA-36-4-8R | 4 | 36 | 90 | Robin | 8.0 | 75-155 | 166.0 | 75.0 | 206.0 | 93.0 |
| | HPHA-36-4-8H | 4 | 36 | 90 | Honda | 8.0 | 75-155 | 171.0 | 77.0 | 211.0 | 96.0 |
| | HPHA-46-4-11H | 4 | 46 | 117 | Honda | 11.0 | 65-140 | 250.0 | 113.0 | 310.0 | 141.0 |
| HD-SERIES | HDA-48-4-11H | 4 | 48 | 122 | Honda | 11.0 | 65-140 | 295.0 | 134.0 | 355.0 | 161.0 |
| | HDA-48-4-13H | 4 | 48 | 122 | Honda, variable speed clutch | 13.0 | 35-180 | 315.0 | 143.0 | 365.0 | 166.0 |

© COPYRIGHT 2006, MULTQUIP INC.

Lifting Bales

1472..... Fits all BA, HPHA, HPLA series with Honda engines and 9-HP Robin engines
 1846..... Fits all JA, M, E series with gasoline engines
 9151..... Fits HDA trowels with 13-HP engines
 10157..... Fits all 11-HP Honda trowels (standard on HDA models)

Grinding Accessories

GA985 Grinding Stones
 GD485 Grinding Disk

Your Multiquip dealer is:



MULTIQUIP INC.
 POST OFFICE BOX 6254
 CARSON, CA 90749
 310-537-3700 • 800-421-1244
 FAX: 310-537-3927
 E-MAIL: mq@multiquip.com
 www.multiquip.com